

HardiePanel™ compressed sheet

What is it?

A structural flooring substrate for ceramic tile finishes over timber or lightweight steel floor joists; it's made from durable compressed fibre cement.

Where do you use it?

As an internal substrate for tiled wet-area floors and an external substrate for tiled balconies, verandas and decks, in both residential and commercial buildings. It's a durable, moisture-resistant alternative to particleboard and plywood substrates, and a lightweight alternative to concrete.

What are the key benefits?

Durability.

The compressed sheet structure delivers a high level of durability and stability, making it an ideal flooring substrate for both internal and external use, in residential and commercial buildings.

Versatility.

HardiePanel compressed sheet can also be used as formwork in a range of industrial and commercial applications such as bridges and roadworks. To add to this, it's deemed non-combustible in accordance with the provisions of the Building Code of Australia, and can be used for floors in bushfire-prone areas.

Security.

HardiePanel compressed sheet is resistant to damage from termites, rot and fire. A 10-year product warranty gives peace of mind.

Length (mm)	Width (mm)	Thickness (mm)	Mass (kg/m ²)
1800	900	15mm	28.8
1800	1200		
2100	1200		
2400	900		
2400	1200		
2700	1200		
3000	900		
3000	1200		
1800	900	18mm	34.5
1800	1200		
2100	1200		
2400	900		
2400	1200		
3000	900		
3000	1200		
2400	1200	24mm	46.9

